



Super Whip Vacuum Hose

Features & Benefits

- ◆ Specially designed for the work end of a vacuum conveying line.
- ◆ Carbon filled inner tube insures static conductivity.
- ◆ Lightweight, easy to handle, flexible, kink resistant, and abrasion resistant.
- ◆ Hand built construction of wire reinforced natural rubber ensures long life.
- ◆ Soft hose cuffs simplify coupler installation.
- ◆ Capable of handling wet, dry or hot materials. (Temperature rating of -40° to 250°F). Doesn't get stiff or crack in cold weather.
- ◆ Smooth bore minimizes friction loss for maximum material loading rates.
- ◆ Available in sizes from 2 1/2" to 8" ID. 20 and 50 foot sections.



Super Whip Vacuum Hose

Problem:



Specifications

Part No.	Order No.	Diameter(In.)	Length (Ft.)	TUBE		REINFORCEMENT		Bend Radius (In.)	Temp. Rating (°F)	Vacuum Rating (In. Hg)	WEIGHT (LBS.)	
				Thk.	Mat'l.	Plies	Wire				Per Ft.	Per Length
10-925-20	WH-2 1/2-20-GP	2 1/2	20		Static			3.75		27	0.8	16
10-930-20	WH-3-20-GP	3	20	3/32"	Conductive			4.5	-40°	27	1.1	22
10-940-20	WH-4-20-GP	4	20		Natural	1	Steel	6.0	to	27	1.7	34
10-960-20	WH-6-20-GP	6	20		Rubber			8.5	+250°	24	2.5	50
10-980-20	WH-8-20-GP	8	20					11.0		20	3.5	70
10-925-50	BCM-2 1/2-50-XL	2 1/2	50		Static			3.75	-40°	27	0.8	40
10-930-50	BCM-3-50-XL	3	50	3/32"	Conductive	1	Steel	4.5	to	27	1.1	55
10-940-50	BCM-4-50-XL	4	50		Natural			6.0	+250°	27	1.7	85
10-960-50	BCM-6-50-XL	6	50		Rubber			8.5		24	2.5	125

Specifications subject to change without notice.

Solution:

*Shock-Free
Lightweight
Fast-Vac Vacuum
Hose!*



FAST-VAC™ P. O. Box 241 • Hartland, WI 53029

Ph: 800-558-2280 Fax: 800-558-2281
Int'l Ph: 262-367-2280 Int'l Fax: 262-367-7245 email: sales@fast-vac.com

www.fast-vac.com

